



Pneumatic Fittings Specifications

Mild Steel • Aluminum • Stainless • Galvanized • All Tubing & Pipe Sizes




Lateral

Sizes	30°		45°		60°	
	A	B	A	B	A	B
1 1/2	10	16	10	16	8	14
1 3/4	10	16	10	16	8	14
2	10	16	10	16	8	14
2 1/4	10	16	10	16	8	14
2 1/2	12	18	10	16	8	16
3	12	18	10	16	8	16
3 1/2	16	24	12	20	12	24
4	16	24	12	20	12	24
4 1/2	18	26	16	24	16	24
5	18	30	18	24	18	24
6	24	36	20	30	20	30
8	28	36	20	36	20	36




Tees

Sizes	B	C
1 1/2	12	6
1 3/4	12	6
2	12	6
2 1/4	12	6
2 1/2	16	8
3	16	8
3 1/2	16	8
4	20	8
4 1/2	24	10
5	24	10
6	24	10
8	28	12



Parallel Wye


Sizes	B
1 1/2	16
1 3/4	16
2	16
2 1/4	16
2 1/2	16
3	16
3 1/2	20
4	20
4 1/2	24
5	24
6	30



90° Ty


Sizes	B
1 1/2	16
1 3/4	16
2	16
2 1/4	16
2 1/2	16
3	16
3 1/2	20
4	20
4 1/2	24
5	24
6	30

Order Pneumatic fittings by O.D., type of metal, wall thickness, radius and/or degree as applicable




Matches
150 lb.
Flange
Pattern


Flange Tube Adapter
(specify sizes)




Square 90°
(specify OD)




Threaded Adapter
(male & female)




Dual Straight Through Lateral
(specify degree)



Segmented Elbow
(specify radius & number of segments)



True Wye
(specify degree)



Coped Wye
(specify radius)



Transition
(specify outside diameters)

Also Available - Drop Line Tees & Common Line Diverters